

[54] PORTABLE APPARATUS HAVING A CABLE GUIDE DUCT MOUNTED BETWEEN A BASE HOUSING AND A DISPLAY AND PIVOTALLY CONNECTED TO THE BASE HOUSING

[75] Inventor: Katumaru Sasaki, Ohme, Japan

[73] Assignee: Kabushiki Kaisha Toshiba,
Kanagawa, Japan

[21] Appl. No.: 92,127

[22] Filed: Sep. 2, 1987

[30] Foreign Application Priority Data

Sep. 4, 1986 [JP] Japan 61-135873

[51] Int. Cl.⁴ G06F 1/00

[52] U.S. Cl. 364/708

[58] Field of Search 364/708-710;
340/711

[56] References Cited

U.S. PATENT DOCUMENTS

4,496,943	1/1985	Greenblatt	340/711
4,497,036	1/1985	Dunn	364/708
4,571,456	2/1986	Paulsen et al.	340/700 X
4,739,316	4/1988	Yamaguchi et al.	340/711
4,742,478	5/1988	Nigro, Jr. et al.	364/708

FOREIGN PATENT DOCUMENTS

60-160418	8/1985	Japan	364/708
60-214030	10/1985	Japan	364/708
60-225919	11/1985	Japan	364/708
60-225920	11/1985	Japan	364/708
61-7971	1/1986	Japan	364/708

Primary Examiner—Gary V. Harkcom

Assistant Examiner—Tan V. Mai

Attorney, Agent, or Firm—Finnegan, Henderson,
Farabow, Garrett, & Dummer

[57] ABSTRACT

Laptop computer apparatus includes a base housing, a display housing, a cable and a cable guide duct. The base includes a front upper surface having a keyboard. The display portable apparatus and a closed position for covering the keyboard. The cable is introduced from the base housing into the display housing through the cable guide duct. The cable guide duct includes a first surface and a second surface. When the display housing is rotated to the open position, the first surface is exposed. When the display housing is rotated to the closed position, the second surface is exposed.

12 Claims, 3 Drawing Sheets

